

EV Select

Spreader

Perfect for maintaining parking lots, roads, or highways, the versatile EV Select efficiently handles de-icing materials used by municipal fleets, landscapers, and private contractors. This highly customizable spreader is designed to integrate easily with dump bodies and flatbeds with a minimum 20,000 lb. GVM.

Highlights

- High-volume inverted "V" shape increases performance and reduces wear
- Drop-n-loc[™] design allows for **safe, easy removal of the top screens**
- Maintenance-free poly idler carries a 10-year warranty
- Swing-up spinner system with 18" 20" spinner disk, available in carbon, polyurethane, and stainless steel

Your benefits

- Perfect for general spreading and a workhorse in municipal fleets
- Precision placement of material with our advanced baffle system
- Optional high-torque gearbox handles rock salt, sand, salt/sand mix, 3/8 chips, magnesium chloride, Clear Path Ice Melt, and treated rock salt
- Available with pre-wet system





Performance features

Concept

The Swenson family of V-box spreaders represents the ultimate in manufacturing quality, performance, and reliability. These highly customizable products allow you to tailor your spreaders to your specific needs. Built with a versatile design, the EV Select Series of spreaders enables you to customize options without adding additional build time. The EV Select Large V-Box Spreaders are among the most advanced and reliable systems available.



Dosage and Conveyor Systems

Swenson spreaders are available in multiple configurations with customizable power equipment. Options include:

- Conveyors Chain, belt-over-chain
- Gearbox 6:1, 25:1, 50:1
- Sprocket Choose from 6- or 8-tooth sprocket systems with 1 1/2" or 2" drive shaft
- Spinner Motor Top-mounted or bottom-mounted spinner motors
- Spinner Swing-up or standard spinner options







Pre-Wet Systems

The EV Select Large V-Box Spreader is available with hydraulic or electric prewet systems, providing the right solution for the materials you use.



Specifications

- Size: Many units have been built up to 84" wide in various heights. Lengths range from 8' to 25'
- **Capacity**: Capacity will vary based on the width, height, and length of the hopper. Unit capacity can range from 5 cu yds to more than 12 for custom requests
- Drive: Hydraulic or electric
- Conveyor: Chain, belt-over-chain, and single or dual auger conveyors
- Construction: 10-gauge carbon steel, 12-gauge stainless steel
- Spread Width: 3-40 ft.
- Safety: Drop-n-loc[™]
- Accessories: Ladder, work lights, cab shields, tarp kit, vibrator, chain oiler, leg stands, pre-wet system, anti-ice systems, gas-over-hydraulic



Related products

EV Dual Auger Spreader

EVA Auger Spreader



Technical data

	EV Select 100	EV Select 150	EV Select 200
Hopper			
Hopper capacity	4 - 9 m³	4 - 9 m ³	4 - 9 m³
Mounting/demount system			
Mounting/demount system	Demount legs / Fixed-mounted	Demount legs / Fixed-mounted	Demount legs / Fixed-mounted
Drive system			
Type of drive	Vehicle hydraulics	Vehicle hydraulics	Vehicle hydraulics
			_
	EV Select Aviation	EV Select Combo Liquid Dry	
Hopper			
Hopper capacity	3 - 11 m ³	5 - 7 m³	
Mounting/demount system			
Mounting/demount system	Demount legs / Fixed-mounted	Demount legs / Fixed-mounted	
Drive system			-
Type of drive	Vehicle hydraulics	Vehicle hydraulics	



© Aebi Schmidt Group www.aebi-schmidt.com

Aebi Schmidt Holding AG CH-8050 Zurich, Switzerland

All rights reserved. Technical data is subject to change. Illustrations are not binding. Errors and amendments excepted.

Document created on 17 FEB 2025

